

Number of Cores	Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight
No.	mm ²	mm	Kg / Km
2	1.5 rm	10.0	130
	2.5 rm	11.4	170
	4 rm	13.0	240
	6 rm	14.0	300
	10 rm	17.0	445
	16 rm	19.0	550
	25 sm	19.0	680
	35 sm	21.0	900
	50 sm	23.0	1180
	70 sm	26.0	1620
3	1.5 rm	10.5	150
	2.5 rm	12.5	200
	4 rm	13.5	285
	6 rm	15.0	360
	10 rm	18.0	520
	16 rm	20.0	665
	25 sm	21.0	1050
	35 sm	23.0	1290
	50 sm	26.5	1700
	70 sm	29.5	2360
	95 sm	35.0	3240
	120 sm	37.0	4000
	150 sm	41.0	5000
	185 sm	46.0	6100
240 sm	51.0	7900	
300 sm	58.0	9770	
4	1.5 rm	11.5	180
	2.5 rm	13.0	240
	4 rm	14.5	340
	6 rm	16.0	445
	10 rm	19.5	690
	16 rm	22.0	920
	25 sm	24.0	1285
	35 sm	26.5	1695
	50 sm	30.0	2255
	70 sm	34.0	3120
	95 sm	39.5	4270
	120 sm	44.0	5300
	150 sm	47.5	6460
	185 sm	52.0	8080
	240 sm	58.0	10500
300 sm	65.0	13040	
400 sm	73.3	16600	
5 (Colour)	1.5 rm	12.0	230
	2.5 rm	13.8	285
	4 rm	15.8	400
	6 rm	17.1	570
	10 rm	20.7	760
	16 rm	23.5	1260
5	1.5 rm	12.0	230
7		13.0	260
10		14.8	380
12		15.8	440
19		18.6	635
27		22.0	850
37		24.5	1120
40		25.2	1180
5	2.5 rm	13.8	285
7		15.0	380
10		17.0	460
12		18.2	565
19		21.8	860
27		25.5	1165
37		29.0	1555
5	4 rm	15.8	400
7		17.0	515
10		19.8	730
12		21.5	850
19		25.5	1260
27		29.6	1730

rm : Stranded Circular Non-Compacted

sm : Stranded Shaped

Notes :

1. For 7 cores & above cables with earth core (Green/Yellow) are available upon request.
2. Any other cores (up to 48 cores) not indicated in this table are also available upon request.