

No. of Core & Nominal Area of Conductor	FRIC -300		FRIC -300A	
	Approx. Overall Diameter	Approx. Weight	Approx. Overall Diameter	Approx. Weight
No. X mm <sup>2</sup>	mm	Kg / Km	mm	kg / Km
1 X 2 X 1.0	7.8	88	12.6	325
1 X 3 X 1.0	8.4	102	13.2	360
2 X 2 X 1.0	9.4	140	14.2	422
4 X 2 X 1.0	16.6	275	22.8	928
6 X 2 X 1.0	20.1	400	26.2	1150
8 X 2 X 1.0	22.0	510	28.8	1470
10 X 2 X 1.0	24.1	630	31.0	1660
1 X 2 X 1.5	9.0	110	13.0	375
1 X 3 X 1.5	9.5	130	14.3	421
2 X 2 X 1.5	10.6	165	15.4	496
4 X 2 X 1.5	19.0	350	25.4	1110
6 X 2 X 1.5	23.5	545	29.6	1390
8 X 2 X 1.5	25.5	700	32.4	1790
10 X 2 X 1.5	28.0	820	35.2	2060
1 X 2 X 2.5	10.3	140	15.2	450
1 X 3 X 2.5	10.9	175	15.7	508
2 X 2 X 2.5	12.5	230	17.5	625
4 X 2 X 2.5	21.3	470	27.8	1310
6 X 2 X 2.5	26.8	720	33.8	1890
8 X 2 X 2.5	29.5	930	36.8	2220
10 X 2 X 2.5	32.5	1130	39.8	2600