

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		FRIC-200C-M	FRIC-200Q-M			FRIC-200C-M	FRIC-200Q-M			FRIC-200C-M	FRIC-200Q-M
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km
1 X 2 X 0.75	10.1	148	143	1 X 2 X 1.0	10.7	163	158	1 X 2 X 1.5	11.4	187	181
1 X 3 X 0.75	10.8	174	169	1 X 3 X 1.0	11.2	190	185	1 X 3 X 1.5	12.0	221	215
1 X 4 X 0.75	11.6	200	194	1 X 4 X 1.0	12.1	223	217	1 X 4 X 1.5	12.9	263	256
3 X 2 X 0.75	16.9	317	308	3 X 2 X 1.0	17.4	342	333	3 X 2 X 1.5	19.4	464	448
4 X 2 X 0.75	19.1	379	368	4 X 2 X 1.0	20.4	478	462	4 X 2 X 1.5	22.0	565	546
6 X 2 X 0.75	22.6	557	538	6 X 2 X 1.0	23.9	636	616	6 X 2 X 1.5	25.8	768	746
7 X 2 X 0.75	22.6	589	570	7 X 2 X 1.0	23.9	675	655	7 X 2 X 1.5	25.8	821	799
8 X 2 X 0.75	25.0	680	659	8 X 2 X 1.0	25.3	736	715	8 X 2 X 1.5	26.9	904	881
10 X 2 X 0.75	27.2	792	769	10 X 2 X 1.0	28.6	888	864	10 X 2 X 1.5	29.8	1080	1055
12 X 2 X 0.75	29.4	907	882	12 X 2 X 1.0	31.1	1038	1012	12 X 2 X 1.5	32.6	1247	1219
14 X 2 X 0.75	31.5	1024	997	14 X 2 X 1.0	33.2	1153	1125	14 X 2 X 1.5	34.8	1403	1373
16 X 2 X 0.75	33.3	1130	1101	16 X 2 X 1.0	35.1	1276	1245	16 X 2 X 1.5	37.0	1568	1536
19 X 2 X 0.75	36.1	1294	1263	19 X 2 X 1.0	37.9	1465	1432	19 X 2 X 1.5	40.0	1806	1771
20 X 2 X 0.75	36.8	1342	1310	20 X 2 X 1.0	38.8	1520	1486				

Note : * SST = Cables with lapped inner covering and a single sheath design.