

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		MIM-200C	MIM-200Q			MIM-200C	MIM-200Q			MIM-200C	MIM-200Q
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km
2 X 0.5	7.5	96	93	7 X 0.75	10.6	197	192	19 X 1.0	16.9	519	506
3 X 0.5	7.8	103	100	8 X 0.75	11.6	222	216	20 X 1.0	17.7	545	532
4 X 0.5	8.3	117	113	10 X 0.75	13.0	267	260	24 X 1.0	19.5	638	623
5 X 0.5	8.8	131	127	12 X 0.75	13.4	294	287	27 X 1.0	19.9	687	670
6 X 0.5	9.5	149	145	16 X 0.75	14.6	356	349	37 X 1.0	22.1	868	850
7 X 0.5	9.5	156	152	19 X 0.75	15.9	445	433	2 X 1.5	9.6	155	151
8 X 0.5	10.6	181	176	20 X 0.75	16.6	467	455	3 X 1.5	10.1	177	172
10 X 0.5	11.6	210	205	24 X 0.75	18.3	547	533	4 X 1.5	10.8	207	201
12 X 0.5	11.9	229	223	27 X 0.75	18.6	583	569	5 X 1.5	11.6	237	232
16 X 0.5	13.2	283	277	37 X 0.75	20.5	724	708	6 X 1.5	12.8	279	272
19 X 0.5	13.8	314	307	2 X 1.0	8.5	125	121	7 X 1.5	12.8	298	292
20 X 0.5	14.4	332	324	3 X 1.0	8.9	139	135	8 X 1.5	14.0	337	330
24 X 0.5	15.7	379	371	4 X 1.0	9.7	166	161	10 X 1.5	16.2	447	435
27 X 0.5	16.0	406	397	5 X 1.0	10.4	189	184	12 X 1.5	16.7	496	483
37 X 0.5	18.2	557	543	6 X 1.0	11.2	214	209	16 X 1.5	18.5	616	601
2 X 0.75	8.1	112	108	7 X 1.0	11.2	227	222	19 X 1.5	19.4	690	675
3 X 0.75	8.5	122	119	8 X 1.0	12.3	256	250	20 X 1.5	20.3	727	711
4 X 0.75	9.0	140	136	10 X 1.0	13.8	309	302	24 X 1.5	22.4	854	836
5 X 0.75	9.8	165	160	12 X 1.0	14.2	341	333	27 X 1.5	22.8	919	901
6 X 0.75	10.6	187	182	16 X 1.0	16.2	465	453	37 X 1.5	25.5	1178	1157

Note : * SST = Cables with lapped inner covering and a single sheath design.