

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		MIP-200C	MIP-200Q			MIP-200C	MIP-200Q			MIP-200C	MIP-200Q
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km
2 X 2 X 0.5	11.7	181	175	8 X 2 X 0.75	19.3	543	527	19 X 2 X 1.0	29.5	1243	1218
3 X 2 X 0.5	12.2	205	199	10 X 2 X 0.75	21.0	632	615	20 X 2 X 1.0	30.3	1309	1283
4 X 2 X 0.5	13.2	240	233	12 X 2 X 0.75	22.8	736	718	24 X 2 X 1.0	32.9	1523	1495
6 X 2 X 0.5	15.6	323	315	14 X 2 X 0.75	24.2	822	802	27 X 2 X 1.0	34.5	1673	1643
7 X 2 X 0.5	15.6	344	335	16 X 2 X 0.75	25.5	908	886	30 X 2 X 1.0	36.2	1836	1805
8 X 2 X 0.5	16.6	379	370	19 X 2 X 0.75	27.5	1045	1021	2 X 2 X 1.5	15.4	296	288
10 X 2 X 0.5	18.6	499	484	20 X 2 X 0.75	28.1	1086	1062	3 X 2 X 1.5	16.9	415	401
12 X 2 X 0.5	20.1	572	555	24 X 2 X 0.75	30.5	1258	1232	4 X 2 X 1.5	18.4	491	476
14 X 2 X 0.5	21.5	645	628	27 X 2 X 0.75	32.0	1377	1349	6 X 2 X 1.5	21.8	667	649
16 X 2 X 0.5	22.6	708	690	30 X 2 X 0.75	33.8	1533	1504	7 X 2 X 1.5	21.8	717	699
19 X 2 X 0.5	24.2	800	780	2 X 2 X 1.0	13.8	247	239	8 X 2 X 1.5	22.8	793	775
20 X 2 X 0.5	24.9	847	826	3 X 2 X 1.0	14.6	297	289	10 X 2 X 1.5	25.0	949	928
24 X 2 X 0.5	27.0	982	959	4 X 2 X 1.0	15.9	353	344	12 X 2 X 1.5	27.0	1092	1070
27 X 2 X 0.5	28.3	1069	1045	6 X 2 X 1.0	19.3	529	514	14 X 2 X 1.5	28.9	1247	1222
30 X 2 X 0.5	29.7	1171	1146	7 X 2 X 1.0	19.3	567	551	16 X 2 X 1.5	30.5	1380	1354
2 X 2 X 0.75	12.8	209	202	8 X 2 X 1.0	20.6	636	620	19 X 2 X 1.5	32.9	1593	1565
3 X 2 X 0.75	13.7	257	250	10 X 2 X 1.0	22.6	756	738	20 X 2 X 1.5	33.8	1682	1653
4 X 2 X 0.75	14.8	301	294	12 X 2 X 1.0	24.4	869	849	24 X 2 X 1.5	36.6	1959	1928
6 X 2 X 0.75	18.0	456	441	14 X 2 X 1.0	25.9	975	954	27 X 2 X 1.5	38.5	2149	2116
7 X 2 X 0.75	18.0	484	470	16 X 2 X 1.0	27.5	1092	1069	30 X 2 X 1.5	40.6	2383	2349

Note : * SST = Cables with lapped inner covering and a single sheath design.