

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		MIC-200C	MIC-200Q			MIC-200C	MIC-200Q			MIC-200C	MIC-200Q
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km
1 X 2 X 0.5	7.5	97	94	7 X 2 X 0.75	16.5	367	358	19 X 2 X 1.0	28.5	1040	1015
1 X 3 X 0.5	7.8	99	96	8 X 2 X 0.75	17.8	454	440	20 X 2 X 1.0	29.1	1078	1053
1 X 4 X 0.5	8.3	118	115	10 X 2 X 0.75	19.9	544	527	24 X 2 X 1.0	31.6	1247	1220
3 X 2 X 0.5	11.6	182	177	12 X 2 X 0.75	21.5	617	600	27 X 2 X 1.0	33.1	1366	1337
4 X 2 X 0.5	12.8	213	207	14 X 2 X 0.75	23.0	700	681	30 X 2 X 1.0	35.0	1516	1486
6 X 2 X 0.5	15.1	285	277	16 X 2 X 0.75	24.2	770	749	1 X 2 X 1.5	9.5	156	151
7 X 2 X 0.5	15.1	300	292	19 X 2 X 0.75	25.9	868	845	1 X 3 X 1.5	10.1	178	174
8 X 2 X 0.5	15.9	327	319	20 X 2 X 0.75	26.7	913	891	1 X 4 X 1.5	10.8	208	203
10 X 2 X 0.5	18.0	436	421	24 X 2 X 0.75	28.9	1058	1033	3 X 2 X 1.5	15.2	318	310
12 X 2 X 0.5	19.4	493	478	27 X 2 X 0.75	30.3	1147	1121	4 X 2 X 1.5	17.7	442	428
14 X 2 X 0.5	20.6	547	530	30 X 2 X 0.75	31.9	1254	1227	6 X 2 X 1.5	20.5	585	569
16 X 2 X 0.5	21.9	610	592	1 X 2 X 1.0	8.5	127	123	7 X 2 X 1.5	20.5	624	607
19 X 2 X 0.5	23.4	683	664	1 X 3 X 1.0	8.9	140	136	8 X 2 X 1.5	21.4	688	671
20 X 2 X 0.5	23.9	706	686	1 X 4 X 1.0	9.7	167	163	10 X 2 X 1.5	23.6	823	803
24 X 2 X 0.5	25.9	816	794	3 X 2 X 1.0	13.4	248	241	12 X 2 X 1.5	25.8	951	930
27 X 2 X 0.5	27.1	885	862	4 X 2 X 1.0	15.3	308	299	14 X 2 X 1.5	27.4	1060	1037
30 X 2 X 0.5	28.7	987	963	6 X 2 X 1.0	18.3	456	441	16 X 2 X 1.5	29.1	1191	1166
1 X 2 X 0.75	8.0	112	108	7 X 2 X 1.0	18.3	483	468	19 X 2 X 1.5	31.2	1352	1325
1 X 3 X 0.75	8.5	123	120	8 X 2 X 1.0	19.3	527	512	20 X 2 X 1.5	32.1	1423	1396
1 X 4 X 0.75	9.0	142	138	10 X 2 X 1.0	21.7	637	619	24 X 2 X 1.5	34.8	1660	1630
3 X 2 X 0.75	12.6	214	208	12 X 2 X 1.0	23.4	727	708	27 X 2 X 1.5	36.6	1815	1784
4 X 2 X 0.75	14.1	265	257	14 X 2 X 1.0	25.0	823	802	30 X 2 X 1.5	38.7	2108	2064
6 X 2 X 0.75	16.5	346	337	16 X 2 X 1.0	26.4	906	884				

Note : * SST = Cables with lapped inner covering and a single sheath design.