

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		MIM-210C	MIM-210Q			MIM-210C	MIM-210Q			MIM-210C	MIM-210Q
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km
2 X 0.5	7.5	93	90	7 X 0.75	10.6	193	188	19 X 1.0	16.9	510	497
3 X 0.5	7.8	100	97	8 X 0.75	11.6	217	211	20 X 1.0	17.7	536	522
4 X 0.5	8.3	114	110	10 X 0.75	13.0	261	254	24 X 1.0	19.5	627	612
5 X 0.5	8.8	128	124	12 X 0.75	13.4	287	280	27 X 1.0	19.9	675	659
6 X 0.5	9.5	145	141	16 X 0.75	14.6	349	341	37 X 1.0	22.1	855	837
7 X 0.5	9.5	153	148	19 X 0.75	15.9	437	425	2 X 1.5	9.6	151	147
8 X 0.5	10.6	177	172	20 X 0.75	16.6	459	446	3 X 1.5	10.1	173	168
10 X 0.5	11.6	205	200	24 X 0.75	18.3	537	523	4 X 1.5	10.8	202	197
12 X 0.5	11.9	224	218	27 X 0.75	18.6	573	558	5 X 1.5	11.6	233	227
16 X 0.5	13.2	277	270	37 X 0.75	20.5	713	696	6 X 1.5	12.8	273	266
19 X 0.5	13.8	308	301	2 X 1.0	8.5	122	118	7 X 1.5	12.8	292	286
20 X 0.5	14.4	325	317	3 X 1.0	8.9	136	132	8 X 1.5	14.0	330	323
24 X 0.5	15.7	371	363	4 X 1.0	9.7	162	157	10 X 1.5	16.2	439	426
27 X 0.5	16.0	398	389	5 X 1.0	10.4	184	179	12 X 1.5	16.7	487	474
37 X 0.5	18.2	548	533	6 X 1.0	11.2	210	204	16 X 1.5	18.5	605	591
2 X 0.75	8.1	109	105	7 X 1.0	11.2	223	217	19 X 1.5	19.4	679	664
3 X 0.75	8.5	119	115	8 X 1.0	12.3	251	245	20 X 1.5	20.3	716	700
4 X 0.75	9.0	137	133	10 X 1.0	13.8	303	296	24 X 1.5	22.4	841	823
5 X 0.75	9.8	161	156	12 X 1.0	14.2	334	327	27 X 1.5	22.8	906	887
6 X 0.75	10.6	183	177	16 X 1.0	16.2	457	444	37 X 1.5	25.5	1162	1141

Note : * SST = Cables with lapped inner covering and a single sheath design.