

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight				
		MC-200Q	MC-200C			MC-200Q	MC-200C			MC-200Q	MC-200C			
No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km	No. X mm ²	mm	Kg/Km	Kg/Km			
1 X 10	rm	10.0	-	190	3 X 6	rm	14.5	356	366	10 X 1.0	rm	15.3	320	330
1 X 16	rm	11.2	-	260	3 X 10	rm	16.8	530	540	12 X 1.0	rm	16.4	360	370
1 X 25	cm	12.5	-	370	3 X 6	rm	19.1	740	760	16 X 1.0	rm	18.1	460	470
1 X 35	cm	14.2	-	480	3 X 25	cm	22.9	1190	1208	19 X 1.0	rm	19.4	520	530
1 X 50	cm	15.7	-	650	3 X 25	sm	20.5	1040	1060	24 X 1.0	rm	21.5	630	640
1 X 70	cm	17.7	-	900	3 X 35	cm	25.3	1543	1564	27 X 1.0	rm	22.6	680	700
1 X 95	cm	19.8	-	1170	3 X 35	sm	22.8	1370	1390	37 X 1.0	rm	25.2	890	910
1 X 120	cm	21.4	-	1440	3 X 50	cm	28.3	1987	2010	5 X 1.5	rm	12.9	220	230
1 X 150	cm	23.4	-	1660	3 X 50	sm	25.5	1800	1820	6 X 1.5	rm	14.0	260	265
1 X 185	cm	25.7	-	2140	3 X 70	sm	29.3	2490	2510	7 X 1.5	rm	14.0	280	285
1 X 240	rm	30.2	-	2770	3 X 95	sm	32.8	3330	3350	8 X 1.5	rm	15.2	340	350
1 X 300	rm	32.9	-	3400	3 X 120	sm	37.3	4210	4250	10 X 1.5	rm	16.6	400	410
2 X 1.0	rm	9.1	110	115	3 X 150	sm	42.4	5140	5180	12 X 1.5	rm	17.6	460	480
2 X 1.5	rm	9.7	130	140	4 X 1.0	rm	10.6	160	165	16 X 1.5	rm	19.8	580	590
2 X 2.5	rm	10.5	156	160	4 X 1.5	rm	11.3	185	190	19 X 1.5	rm	21.0	660	680
2 X 4	rm	11.9	210	220	4 X 2.5	rm	12.3	240	250	24 X 1.5	rm	23.0	810	830
2 X 6	rm	14.0	270	275	4 X 4	rm	14.0	325	330	27 X 1.5	rm	24.2	880	890
2 X 10	rm	16.4	410	420	4 X 6	rm	15.8	460	470	37 X 1.5	rm	27.5	1150	1170
2 X 16	rm	18.6	560	580	4 X 10	rm	18.3	660	680	5 X 2.5	rm	14.4	280	290
2 X 25	cm	21.4	881	898	4 X 16	rm	20.5	950	970	6 X 2.5	rm	15.6	360	370
2 X 25	sm	18.2	760	770	4 X 25	cm	25.1	1508	1529	7 X 2.5	rm	15.6	390	400
2 X 35	cm	24.0	1135	1154	4 X 25	sm	23.3	1350	1370	8 X 2.5	rm	16.7	430	440
2 X 35	sm	20.8	970	990	4 X 35	cm	28.2	1968	1991	10 X 2.5	rm	18.2	520	530
2 X 50	cm	26.6	1444	1466	4 X 35	sm	25.9	1780	1800	12 X 2.5	rm	19.4	600	620
2 X 50	sm	23.5	1270	1290	4 X 50	cm	32.6	2548	2576	16 X 2.5	rm	21.6	760	780
2 X 70	cm	33.1	1982	2008	4 X 50	sm	29.1	2350	2370	19 X 2.5	rm	23.1	870	890
2 X 70	sm	26.7	1730	1750	4 X 70	sm	35.0	3310	3340	24 X 2.5	rm	25.6	1090	1100
2 X 95	sm	29.4	2300	2320	4 X 95	sm	38.6	4440	4460	27 X 2.5	rm	26.8	1180	1190
2 X 120	sm	33.2	2930	2960	5 X 1.0	rm	12.2	180	190	37 X 2.5	rm	30.5	1560	1580
3 X 1.0	rm	9.6	130	140	6 X 1.0	rm	13.0	210	220	5 X 4	rm	16.1	410	420
3 X 1.5	rm	10.3	160	165	7 X 1.0	rm	13.0	220	230	6 X 4	rm	17.6	460	480
3 X 2.5	rm	11.1	200	220	8 X 1.0	rm	14.3	250	260	7 X 4	rm	17.6	520	530
3 X 4	rm	12.6	270	275										

rm : Stranded Circular Non-Compacted

cm : Stranded Circular Compacted

sm : Stranded Shaped

Note : *SST = Cables with lapped inner covering and a single sheath design.