

No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight		No. of Core & Nominal Area of Conductor	Approx. O.D.	Approx. Weight	
		MC-210Q	MC-210C			MC-210Q	MC-210C			MC-210Q	MC-210C
No. X mm²	mm	Kg/Km	Kg/Km	No. X mm²	mm	Kg/Km	Kg/Km	No. X mm²	mm	Kg/Km	Kg/Km
1 X 10 rm	10.0	-	182	3 X 6 rm	14.5	350	360	10 X 1.0 rm	15.3	308	317
1 X 16 rm	11.2	-	247	3 X 10 rm	16.8	503	515	12 X 1.0 rm	16.4	349	360
1 X 25 cm	12.5	-	355	3 X 16 rm	19.1	703	717	16 X 1.0 rm	18.1	441	453
1 X 35 cm	14.2	-	455	3 X 25 cm	22.9	1173	1192	19 X 1.0 rm	19.4	497	511
1 X 50 cm	15.7	-	620	3 X 25 sm	20.5	983	997	24 X 1.0 rm	21.5	603	618
1 X 70 cm	17.7	-	842	3 X 35 cm	25.3	1523	1544	27 X 1.0 rm	22.6	734	751
1 X 95 cm	19.8	-	1099	3 X 35 sm	22.8	1290	1306	37 X 1.0 rm	25.2	853	871
1 X 120 cm	21.4	-	1350	3 X 50 cm	28.3	1987	2010	5 X 1.5 rm	12.9	213	218
1 X 150 cm	23.4	-	1636	3 X 50 sm	25.5	1780	1800	6 X 1.5 rm	14.0	267	276
1 X 185 cm	25.7	-	2004	3 X 70 sm	29.3	2465	2490	7 X 1.5 rm	14.0	286	295
1 X 240 rm	30.2	-	2594	3 X 95 sm	32.8	3280	3310	8 X 1.5 rm	15.2	325	335
1 X 300 rm	32.9	-	3189	3 X 120 sm	37.3	4185	4220	10 X 1.5 rm	16.6	381	391
2 X 1.0 rm	9.1	108	112	3 X 150 sm	42.4	5060	5102	12 X 1.5 rm	17.6	443	455
2 X 1.5 rm	9.7	127	131	4 X 1.0 rm	10.6	150	154	16 X 1.5 rm	19.8	551	564
2 X 2.5 rm	10.5	152	157	4 X 1.5 rm	11.3	181	186	19 X 1.5 rm	21.0	635	649
2 X 4 rm	11.9	201	206	4 X 2.5 rm	12.3	232	237	24 X 1.5 rm	23.0	776	792
2 X 6 rm	14.0	253	258	4 X 4 rm	14.0	338	347	27 X 1.5 rm	24.2	924	943
2 X 10 rm	16.4	388	398	4 X 6 rm	15.8	436	447	37 X 1.5 rm	27.5	1100	1119
2 X 16 rm	18.6	533	545	4 X 10 rm	18.3	629	641	5 X 2.5 rm	14.4	270	275
2 X 25 cm	21.4	866	883	4 X 16 rm	20.5	896	911	6 X 2.5 rm	15.6	347	357
2 X 25 sm	18.2	718	730	4 X 25 cm	25.1	1489	1510	7 X 2.5 rm	15.6	375	385
2 X 35 cm	24.0	1117	1137	4 X 25 sm	23.3	1269	1286	8 X 2.5 rm	16.7	412	423
2 X 35 sm	20.8	918	931	4 X 35 cm	28.2	1945	1968	10 X 2.5 rm	18.2	495	507
2 X 50 cm	26.6	1444	1466	4 X 35 sm	25.9	1675	1694	12 X 2.5 rm	19.4	574	587
2 X 50 sm	23.5	1254	1270	4 X 50 cm	32.6	2548	2574	16 X 2.5 rm	21.6	726	741
2 X 70 cm	31.0	1992	2008	4 X 50 sm	29.1	2328	2350	19 X 2.5 rm	23.1	831	847
2 X 70 sm	26.7	1714	1731	4 X 70 sm	35.0	3293	3330	24 X 2.5 rm	25.6	1032	1050
2 X 95 sm	29.4	2280	2300	4 X 95 sm	38.6	4402	4440	27 X 2.5 rm	26.8	1240	1262
2 X 120 sm	33.2	3030	3060	5 X 1.0 rm	12.2	172	177	37 X 2.5 rm	30.5	1481	1503
3 X 1.0 rm	9.6	128	132	6 X 1.0 rm	13.0	200	206	5 X 4 rm	16.1	400	411
3 X 1.5 rm	10.3	151	155	7 X 1.0 rm	13.0	214	219	6 X 4 rm	17.6	464	476
3 X 2.5 rm	11.1	188	193	8 X 1.0 rm	14.3	237	243	7 X 4 rm	17.6	507	519
3 X 4 rm	12.6	252	258								

rm : Stranded Circular Non-Compacted

cm : Stranded Circular Compacted

sm : Stranded Shaped

Note : * SST = Cables with lapped inner covering and a single sheath design.