

No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight
No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km
1 X 50	19.5	750	3 X 16	23.5	1250	5 X 1.5	16.3	510
1 X 70	21.0	1080	3 X 25 *	25.0	1620	5 X 2.5	17.7	605
1 X 95	23.0	1400	3 X 35 *	27.0	2000	5 X 4	19.9	850
1 X 120	25.5	1680	3 X 50 *	29.8	2500	5 X 6	21.5	1010
1 X 150	27.0	1990	3 X 70 *	34.8	3580	5 X 10	25.2	1460
1 X 185	29.0	2400	3 X 95 *	38.0	4540	5 X 16	27.6	1850
1 X 240	33.5	3050	3 X 120 *	42.0	5500	5 X 25	32.4	2600
1 X 300	36.0	3720	3 X 150 *	47.0	6980	5 X 35	35.2	3230
1 X 400	41.0	4830	3 X 185 *	51.5	8440	5 X 50	41.0	4590
1 X 500	45.0	5850	3 X 240 *	58.5	10600	5 X 70	45.0	5850
1 X 630	49.5	7380	3 X 300 *	63.0	12600	7 X 1.5	17.3	590
1 X 800	56.0	9550	4 X 1.5	15.0	430	10 X 1.5	19.9	820
1 X 1000	61.5	11750	4 X 2.5	16.2	510	12 X 1.5	21.0	910
2 X 1.5	13.8	350	4 X 4	18.0	625	19 X 1.5	24.2	1150
2 X 2.5	14.8	410	4 X 6	19.5	720	27 X 1.5	27.9	1600
2 X 4	16.1	490	4 X 10	22.0	1020	37 X 1.5	31.0	1950
2 X 6	17.4	580	4 X 16	25.5	1630	7 X 2.5	19.4	800
2 X 10	20.0	720	4 X 25 *	27.4	2010	10 X 2.5	21.7	1000
2 X 16	22.0	1040	4 X 35 *	30.5	2530	12 X 2.5	22.9	1100
2 X 25 *	21.5	1270	4 X 50 *	33.5	3180	19 X 2.5	27.2	1580
2 X 35 *	23.5	1530	4 X 70 *	38.0	4500	27 X 2.5	30.7	1990
2 X 50 *	26.0	1870	4 X 95 *	43.0	5760	37 X 2.5	34.4	2470
2 X 70 *	29.2	2410	4 X 120 *	48.0	7500	7 X 4	21.1	990
3 X 1.5	14.2	390	4 X 150 *	52.0	8800	10 X 4	24.5	1380
3 X 2.5	15.4	450	4 X 185 *	57.0	10700	12 X 4	25.9	1530
3 X 4	16.8	550	4 X 240 *	64.0	13550	19 X 4	30.0	2010
3 X 6	18.0	660	4 X 300 *	68.0	16200	27 X 4	34.2	2590
3 X 10	21.0	850	4 X 400 *	82.0	21340			