

No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight
No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km
1 X 50	19.5	750	3 X 16	23.5	1270	5 X 1.5	16.3	520
1 X 70	21.0	1080	3 X 25	26.2	1700	5 X 2.5	17.7	620
1 X 95	23.0	1400	3 X 35	28.2	2050	5 X 4	19.9	870
1 X 120	25.5	1690	3 X 50	31.0	2560	5 X 6	21.5	1030
1 X 150	27.0	2000	3 X 70	36.4	3680	5 X 10	25.2	1490
1 X 185	29.0	2420	3 X 95	39.6	4630	5 X 16	27.6	1880
1 X 240	33.5	3060	3 X 120	43.6	5590	5 X 25	32.4	2630
1 X 300	36.0	3730	3 X 150	49.0	7130	5 X 35	35.2	3270
1 X 400	41.0	4850	3 X 185	53.5	8600	5 X 50	41.0	4620
1 X 500	45.0	5870	3 X 240	60.5	10800	5 X 70	45.0	5880
1 X 630	49.5	7400	3 X 300	65.0	12800	7 X 1.5	17.3	600
1 X 800	56.0	9550	4 X 1.5	15.0	440	10 X 1.5	19.9	840
1 X 1000	61.5	11750	4 X 2.5	16.2	520	12 X 1.5	21.0	930
2 X 1.5	13.8	360	4 X 4	18.0	640	19 X 1.5	24.2	1180
2 X 2.5	14.8	420	4 X 6	19.5	740	27 X 1.5	27.9	1630
2 X 4	16.1	500	4 X 10	22.0	1040	37 X 1.5	31.0	1980
2 X 6	17.4	590	4 X 16	25.5	1650	7 X 2.5	19.4	820
2 X 10	20.0	740	4 X 25	28.6	2060	10 X 2.5	21.7	1020
2 X 16	22.0	1110	4 X 35	31.7	2590	12 X 2.5	22.9	1120
2 X 25	22.7	1310	4 X 50	34.7	3260	19 X 2.5	27.2	1610
2 X 35	24.7	1560	4 X 70	39.6	4600	27 X 2.5	30.7	2020
2 X 50	27.2	1920	4 X 95	44.6	5890	37 X 2.5	34.4	2510
2 X 70	30.4	2460	4 X 120	49.6	7650	7 X 4	21.1	1010
3 X 1.5	14.0	400	4 X 150	53.8	9000	10 X 4	24.5	1400
3 X 2.5	15.4	460	4 X 185	58.8	10960	12 X 4	25.9	1560
3 X 4	16.0	560	4 X 240	66.0	13810	19 X 4	30.0	2040
3 X 6	18.0	670	4 X 300	70.0	16600	27 X 4	34.2	2630
3 X 10	21.0	870	4 X 400	84.0	21800			