

No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight
No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km	No. X mm ²	mm	Kg / Km
2 X 1.5	13.0	320	3 X 240 *	55.5	10580	5 X 16	28.0	2000
2 X 2.5	14.0	390	3 X 300 *	60.5	12690	5 X 25	32.1	2710
2 X 4	15.5	480	4 X 1.5	14.0	390	5 X 35	34.8	3350
2 X 6	17.0	570	4 X 2.5	15.0	490	5 X 50	41.0	4650
2 X 10	20.0	900	4 X 4	18.0	730	5 X 70	45.0	5900
2 X 16	22.0	1100	4 X 6	20.0	850	7 X 1.5	16.0	500
2 X 25 *	21.5	1440	4 X 10	23.0	1200	10 X 1.5	18.5	730
2 X 35 *	23.5	1640	4 X 16	25.8	1640	12 X 1.5	19.5	820
2 X 50 *	26.2	2140	4 X 25 *	27.6	2060	19 X 1.5	22.6	1110
2 X 70 *	29.2	2490	4 X 35 *	30.8	2510	27 X 1.5	27.0	1590
3 X 1.5	13.6	350	4 X 50 *	34.5	3470	37 X 1.5	30.0	1960
3 X 2.5	14.0	430	4 X 70 *	38.5	4540	7 X 2.5	18.6	750
3 X 4	16.0	560	4 X 95 *	43.5	5860	10 X 2.5	21.0	960
3 X 6	18.0	750	4 X 120 *	48.0	7470	12 X 2.5	22.5	1090
3 X 10	21.0	1010	4 X 150 *	52.0	8840	19 X 2.5	27.0	1660
3 X 16	23.5	1290	4 X 185 *	57.0	10670	27 X 2.5	31.0	2120
3 X 25 *	25.4	1720	4 X 240 *	64.0	13390	37 X 2.5	34.5	2660
3 X 35 *	26.6	2070	4 X 300 *	68.5	16240	7 X 4	21.0	990
3 X 50 *	30.6	2580	4 X 400 *	80.6	21650	10 X 4	25.0	1440
3 X 70 *	34.5	3600	5 X 1.5	15.0	440	12 X 4	26.5	1610
3 X 95 *	38.5	4620	5 X 2.5	16.5	560	19 X 4	31.0	2200
3 X 120 *	41.5	5560	5 X 4	19.5	830	27 X 4	37.0	3160
3 X 150 *	46.4	6970	5 X 6	20.8	1030			
3 X 185 *	50.4	8350	5 X 10	25.8	1570			