

No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight	No. of Core & Nominal Area of Conductor	Approx. Overall Diameter	Approx. Weight
No. X mm <sup>2</sup>	mm	Kg / Km	No. X mm <sup>2</sup>	mm	Kg / Km	No. X mm <sup>2</sup>	mm	Kg / Km
1 X 10	11.5	260	3 X 6	16.8	520	5 X 50	36.5	3250
1 X 16	12.7	360	3 X 10	19.2	710	5 X 70	42.0	4400
1 X 25	14.5	490	3 X 16	21.4	910	5 X 1.5	14.5	350
1 X 35	15.8	610	3 X 25	23.9	1250	6 X 1.5	16.0	400
1 X 50	17.2	765	3 X 35	25.1	1600	7 X 1.5	16.0	430
1 X 70	19.1	1030	3 X 50	27.9	2040	8 X 1.5	16.8	480
1 X 95	20.3	1325	3 X 70	32.1	2810	10 X 1.5	18.2	550
1 X 120	22.8	1620	3 X 95	36.8	3940	12 X 1.5	19.2	630
1 X 150	24.8	1940	3 X 120	41.4	4790	16 X 1.5	21.5	740
1 X 185	27.2	2400	3 X 150	43.9	5640	19 X 1.5	22.8	850
1 X 240	31.6	3040	4 X 1.5	13.5	310	24 X 1.5	25.0	1000
1 X 300	33.0	3760	4 X 2.5	14.5	370	37 X 1.5	29.4	1410
2 X 1.5	11.9	240	4 X 4	16.5	480	5 X 2.5	16.0	440
2 X 2.5	13.0	290	4 X 6	17.7	610	6 X 2.5	17.1	510
2 X 4	14.2	370	4 X 10	20.5	840	7 X 2.5	17.1	540
2 X 6	16.0	440	4 X 16	23.2	1140	8 X 2.5	18.2	600
2 X 10	18.0	590	4 X 25	25.4	1580	10 X 2.5	19.9	700
2 X 16	20.2	790	4 X 35	28.1	2030	12 X 2.5	21.0	790
2 X 25	20.6	930	4 X 50	31.1	2610	16 X 2.5	23.2	990
2 X 35	21.4	1160	4 X 70	36.0	3660	19 X 2.5	24.9	1080
2 X 50	24.1	1470	4 X 95	40.2	4870	24 X 2.5	27.3	1320
2 X 70	27.1	1980	5 X 6	16.3	715	37 X 2.5	32.4	1850
2 X 95	30.8	2640	5 X 10	18.9	960	5 X 4	17.7	580
3 X 1.5	12.7	260	5 X 16	21.7	1300	6 X 4	19.2	680
3 X 2.5	13.6	330	5 X 25	25.2	1870	7 X 4	19.2	690
3 X 4	14.8	410	5 X 35	27.9	2440			